

PLATIN THD PLUS SAE 15W-40

SHPD engine oil with high power reserves.

Description

PLATIN THD PLUS SAE 15W-40 is a Super High Performance Diesel (SHPD) engine oil. Its exceptionally wide range of applications is reflected in the interaction of selected base oils with advanced additives. Developed specifically for mixed fleets with petrol and diesel engines from different manufacturers in passenger cars, heavy-goods vehicles, work machines and agricultural machinery.

Application

PLATIN THD PLUS SAE 15W-40 is used in petrol and diesel engines from different manufacturers in mixed vehicle fleets according to the manufacturer's specification. Its modern design makes a wide range of applications possible and ensures safe operation under all operating conditions.

Approvals

- Mack EO-N
- MB-Freigabe 228.3/229.1
- Renault RLD-2
- Volvo VDS-3

The quality of this product is equivalent to EU regulations

- ACEA E7
- ACEA A3/B4
- API CI-4/SL
- GLOBAL DHD-1
- JASO DH-1
- Cummins CES 20071/-72/-75/-76/-77/-78
- Detroit Diesel 93K215
- Deutz DQC III-10
- MTU Type 2

Additionally this product is recommended when the following filling instructions are required

- Allison C-4
- CAT ECF-1-a
- Deutz DQC III-05
- Iveco 18-1804 T1/T2-E7
- Mack EO-M PLUS
- MAN M 3275-1

Benefits

- First-class economy grade for multi-functional use in different brands of diesel and Otto engines
- Suitable for both passenger cars and commercial vehicles, as well as agricultural and construction machinery
- It combines the specifications of European, American and Japanese manufacturers
- Eminently suitable for turbocharged engines
- Prevention of adhesion, lacquering and coking of cylinders, pistons, valves and turbochargers in a reliable manner
- Safer year-round operation
- Stable lubricating film, even with hot oil and under excessive loads, and the best wear protection
- Extremely stable to shear stress - 'Stay-in-grade'
- Low oil consumption and increased oxidation protection
- Miscible and compatible with conventional and synthetic engine oils. However, in order to exploit the full product benefits of PLATIN THD PLUS SAE 15W-40, a complete oil change is recommended.

PLATIN THD PLUS SAE 15W-40**Typical characteristics**

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0.878
Kinematic viscosity KV 40	ASTM D-7042	mm ² /s	103
Kinematic viscosity KV 100	ASTM D-7042	mm ² /s	14,3
Viscosity index	ASTM D-7042	-	140
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	235
Pour point	ASTM D-97 / DIN EN ISO 3016	°C	-30
CCS	ASTM D-5293	cP @ °C	6100 @ -20
Total base number	DIN 51639-1	mgKOH/g	11,6
Acid number	-	mgKOH/g	< 1
HTHS	ASTM D4683	mPas	4,0
Sulphated ash	ASTM D874	wt-%	max. 1,6

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guaranty of certain product properties or of the suitability of the product for a specific application. IGAT products are continually improved. Therefore IGAT reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms (www.igat.ag).