

PLATIN HCO SAE 10W-40

Low viscosity engine oil of viscosity grade SAE 10W-40 based on HC synthetic base oils.

Description

PLATIN HCO SAE 10W-40 is a high-performance engine oil of SAE grade 10W-40 produced using HC synthetic oil. Its high level of performance is achieved through the interaction of selected base oils and advanced additives. Eminently suited to Otto and diesel engines, with or without turbocharging.

Application

PLATIN HCO SAE 10W-40 is particularly suitable for vehicles equipped with Otto and diesel engines, with or without turbocharging. It is used in vehicles without an extended maintenance interval. The modern design of PLATIN HCO SAE 10W-40 makes a wide range of applications possible and ensures safe operation under all operating conditions.

Approvals

- MB-Freigabe 229.3
- VW 501 01/505 00
-

The quality of this product is equivalent to EU regulations

- ACEA A3/B4
- API SN
- MB 226.5
- PSA B71 2300
- Renault RN 0700/0710

Additionally this product is recommended when the following filling instructions are required

- API CF
- Fiat 9.55535-G2/D2
- MB 229.1
- VW 500 00

Benefits

- Eminently suitable for turbocharged engines
- Prevention of adhesion, lacquering and coking of cylinders, pistons, valves and turbochargers in a reliable manner
- Safer year-round operation due to outstanding viscosity-temperature behaviour and high shear stability
- Stable lubricating film, even with hot oil and under excessive loads
- Very low oil consumption
- High level of oxidation protection by means of selected HC synthetic oils and special additives
- Reliable protection against 'black sludge'
- Proper functioning of hydraulic tappets (hydraulic valve clearance compensation)
- Miscible and compatible with conventional and synthetic engine oils. However, in order to exploit the full benefits of the product PLATIN HCO SAE 10W-40, a complete oil change is recommended.

PLATIN HCO SAE 10W-40

Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0.862
Kinematic viscosity KV 40	ASTM D-7042	mm ² /s	93,0
Kinematic viscosity KV 100	ASTM D-7042	mm ² /s	14,2
Viscosity index	ASTM D-7042	-	160
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	220
Pour point	ASTM D-97 / DIN EN ISO 3016	°C	-33
CCS	ASTM D-5293	cP @ °C	5300 @ -25
Total base number	DIN 51639-1	mgKOH/g	10,3
Acid number	-	mgKOH/g	< 1
HTHS	ASTM D4683	mPas	4,1

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guaranty of certain product properties or of the suitability of the product for a specific application. IGAT products are continually improved. Therefore IGAT reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms (www.igat.ag).