

PLATIN TG HC SAE 75W-90

Multigrade gearbox oil of performance rating API GL-4/5 for multi-functional use in axle gears and manual gearboxes in passenger cars, heavy-goods vehicles, off-road vehicles and work machines.

Description

PLATIN TG HC SAE 75W-90 is a high-performance gearbox oil of SAE grade 75W-90 produced using HC synthetic oil. It is characterised by a high thermal load capacity and provides a stable lubricating film, even under continuous stress.

Application

PLATIN TG HC SAE 75W-90 is used for conventional manual gearboxes and axle gears in passenger cars, heavy-goods vehicles, off-road vehicles and work machines. Moreover, PLATIN TG HC SAE 75W-90 can also be used in car and articulated drive shafts that require an oil of classification API GL-5.

The quality of this product is equivalent to EU regulations

- API GL-4/5
- MIL-L 2105D
- MAN 342 Type M1/M2
- Volvo 1273.10/97312
- ZF TE-ML 05A, 07A, 08, 12E, 16B/C, 17B, 19B, 21A

Additionally this product is recommended when the following filling instructions are required

- CNH New Holland NH 520 A
- Ford M2C 197-A/9102-A
- John Deere J 11 E
- MB 235.0/235.1
- NATO O-226
- SDFG OP 1705
- Steyr B-101
- Volvo 97310

Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0.855
Kinematic viscosity KV 40	ASTM D-7042	mm ² /s	74
Kinematic viscosity KV 100	ASTM D-7042	mm ² /s	15,6
Viscosity index	ASTM D-7042	-	226
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	194
Pour point	ASTM D-97 / DIN EN ISO 3016	°C	-39

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guaranty of certain product properties or of the suitability of the product for a specific application. IGAT products are continually improved. Therefore IGAT reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms (www.igat.ag).

Benefits

- Outstanding protection against wear and corrosion
- High temperature and oxidation stability due to selected HC synthetic oils and special additives
- Extremely stable to shear stress - 'Stay-in-grade'
- Stable lubricating film, even with very hot oil and under very high loads. As a result, reduced wear and lower gearbox noise
- The favourable cold viscosity ensures improved shifting ability, fast lubrication and low 'cold wear'
- Miscible and compatible with conventional and synthetic gearbox oils. However, in order to exploit the full product benefits of PLATIN TG HC SAE 75W-90, a complete gearbox oil change is recommended.